

**1**

Quarter turn actuators for dampers and valves

**ExMax**  
**RedMax**



- 5...150 Nm
- 3...150 sec/90°
- On-off, 3-pos
- modulating
- with/without spring return

**2**

Failsafe linear valve actuators

**ExMax + LIN**  
**RedMax + LIN**



- 500...3.000 N
- 7,5...42 mm stroke
- 0,1...15 sec/mm
- On-off, 3-pos
- modulating
- with spring return

**3**

Linear valve actuators

**ExRun**  
**RedRun**




- 500...10.000 N
- 5...60 mm stroke
- 2...15 sec/mm
- On-off, 3-pos
- modulating

**4**

Temperature and humidity sensors

**ExCos-D**  
**RedCos-D**




- -40°C...+125°C
- 0...100 %rH
- full range adjustable

**5**

Pressure/differential pressure sensors

**ExCos-P**  
**RedCos-P**



- ± 100...± 7.500 Pa
- full range adjustable

**6**

Filter monitoring, fan belt protection

**ExBin-P**  
**RedBin-P**




- 0...5.000 Pa
- Pressure/Differential pressure
- Fan-belt protection
- Filter protection
- 1- or 2-stage switching point

**7**

Thermostats, humidistats, Frost protection

**ExBin-D**  
**RedBin-D**



- -40°C...+125°C
- 0...100 %rH
- 1- or 2-stage


**ExBin-FR**  
**RedBin-FR**

- -10°C...+15°C
- Capillary: 3 m, 6 m
- 1-stage switching point

**8**

Controller

**ExReg-V**  
**Differential pressure**



- 0...300 Pa (VAV)

**ExReg-D**  
**Temperature/Humidity**

- -40°C...+125°C
- 0...100 %rH